

**TATA MOTORS**  
Connecting Aspirations



# PRIMA 3338.K

[www.tatamotors.com](http://www.tatamotors.com)





# Prima 3338.K

## SPECIFICATIONS

Model	Prima 3338.K
Drive	8x4
Max GCW (Kg)	33000
Max. FAW (Kg)	15000
Max. Raw (Kg)	18000
Tare Weight (CBC)	11200
Engine Type	CUMMINS 8.9L ISLe 375 Euro-III
Max power	370 BHP @ 2100 rpm
Max torque	1550 Nm at 1200-1400 rpm
Clutch	Pneumatic assisted 430 mm Organic
Gear box	Eaton ES15409-DD 9 Speed
Crawler	14.39
FGR	10.04
TGR	1
Reverse	14.41
Rear Axle	RA 210 HRT
RAR	7.246
Front axle	I Beam - 7.5T X 2
Brake Type	Full Air Dual circuit - S Cam with ABS & Auto Slack Adjuster
Auxillary Braking System	Engine Level Jake Brake

Chassis (mm)	320X90X8
Front Suspension	Parabolic- 20T
Rear Suspension	48T- Two Spring balance beam bogie with semi elliptic multi leaf rubber mounted springs, torque rods and v rods at rear
Tyre size	12R24 - Mining
Ground Clearance (mm)	358
Wheel base (mm)	5250
TCD (mm)	22274
Vehicle Overall Length (wt. Body) (mm)	9257
Vehicle Overall Width (wt. Body) (mm)	2593
Overall Height (wt. Body) (mm)	3486
Max.Greadability @ 1st Gear	54%
Top Speed	66 KMPH
Suitable Body Options	19 Cu M - Scoop
Fuel Tank	260 L Rectangular Shape

### TATA MOTORS LIMITED

International Business,  
A Block, Shivsagar Estate, Dr A B Road, Worli,  
Mumbai 400018. India.  
Tel : 91 22 67577200, Fax : 91 22 67577225  
Website: [www.tatamotors.com](http://www.tatamotors.com)

Tata Motors reserves the right to change and vary the design, technical specifications at any time, without prior notice, as per the Company's policy of continuous product improvement. The illustrations may show accessories and items of optional equipment which are not part of standard specifications. Colours may vary slightly from those shown, owing to limitations of printing process.