



BUILT TO CARRY MORE, MILE AFTER MILE

TATA LPT 1216













5yr/500,000 km Driveline Warranty

TATA LPT 1216

ENGINE	
Model	TATA 697 TIC (Euro 2)
Capacity	6l, 6 Cylinder
Туре	Turbocharged Intercooler
Power (kW at r/min)	118 @ 2,400
Torque (Nm at r/min)	550 @ 1,500-1,700
TRANSMISSION	
Model	GBS - 600
Shift	Manual
No. of gears	6+1
First gear ratio	6.58
Top gear ratio	0.77
DRIVE AXLE	
Reduction type	Single
Final ratio	5.29
CLUTCH	
Туре	Single
Diameter (mm)	352
BRAKES	
Туре	Dual Circuit full air S-Cam
Front	Drums
Rear	Drums
Anti-lock braking system (ABS)	Standard

MAJOR DIMENSIONS	
Overall Height (mm)	2,473
Overall Length (mm)	8,335
Overall Width (mm)	2,270
Front Overhang (mm)	1,175
Rear Overhang (mm)	2,285
Wheelbase (mm)	4,830
MASS	
GVM (kg)	11,500
V (kg)	11,500
GCM (kg)	14,900
D/T (kg)	14,900
Permissible body + payload (kg)	6,020
Tare - total (T) (kg)	5,480
Permissable Rear axle weight (kg)	7,500
Permissable Front axle weight (kg)	4,000
Manufacturers Rear axle weight (kg)	7,500
Manufacturers Front axle weight (kg)	4,000
FUELTANK	
Fuel Tank Capacity (Litre)	160
TYRES	
Tyres	8.25R20-14PR

Available in following applications:



